The following windlasses are offered as options:

Yacht	Option/model	Manufacturer	Chain Size
Moody 31	-	-	-
Moody 336	*Royal	Lofrans	8mm
Moody 35	*Royal *Seawolf 520	Lofrans Simpson Lawrence	8m 5/16"
Moody 376	Royal *Seawolf 520	Lofrans Simpson Lawrence	8mm5/16"
Moody 38	Royal *Seawolf 520	Lofrans Simpson Lawrence	5/16"8mm
Moody 425	Royal *Seawolf 520	Lofrans Simpson Lawrence	10mm 9.5mm
Moody 44	Royal *Seawolf 520	Lofrans Simpson Lawrence	10mm9.5mm
Eclipse 33	Anchoman (gypsy only) *Power 700 (gypsy only -12V)	Simpson Lawrence Simpson Lawrence	5/16" 5/16"
Eclipse 38	Power 700 (gypsy only -12V)	Simpson Lawrence	9.5mm
Eclipse 43	Power 1000 (gypsy only -12V)	Simpson Lawrence	9.5mm

^{*} Not fitted as standard - 'Seawolf' to be replaced March 1991.

Using the windlass

It is recommended that your anchor chain is suitably marked to indicate the amount of chain you have out while at anchor.

When lying at anchor in a heavy swell the chain will snatch either causing chain slip or excessive loads to be applied to the windlass. For safety it is recommended that a rope bridle be applied to transfer the load to a cleat.

Below decks

Upholstery

Your yacht has been upholstered with either the Christiana, Ravenna, Dash or Onyx range of materials. They all meet the Fire and Safety Regulation Act and have been tested to BS5852 PTI. For information on care of your upholstery refer to the maintenance section.