SPECIFICATION

OF THE

MOODY 36 DECK SALOON

U
-
G
[2
A

BUILDER

MARKETED BY

ANGUS S PRIMROSE

MARINE PROJECTS (HILDOWYTH) LIMITED

NEW BOAT SALES, SWANWICK SHORE ROAD, SWANWICK, SOUTHAMPTON HAMPSHIRE, SO3 7ZL O topol MOODY & SOUTHAMPION, SON LIMITED,

TELEX: TELEPHONE: LOCKS HEATH (04895) 477536 6116

DIMENSIONS

DISPLACEMENT FUEL CAPACITY BEAM LWI LOA WATER CAPACITY DRAFT 14,700 lbs 50 gallons 60 301 100 m 1284" Un gallons gallons 6,667.92k 227 litres 273 litres 10.97m 9.14m 3.76m 1.52m

NO. 1 GENOA STORM JIB WORKING JIB MAIN 263 467 94 243 22.58 24.43 8.39 73 sq.m. sq.m. sq.m. sq.m.

WORKING JIB MAINSAIL STANDARD

SAIL AREAS

GENERAL

Hull and superstructure in GRP to Lloyd's specification, 6/7 berth, three cabins including deck saloon. Sloop rig, diesel inboard engine, separate toilet compartment with shower, second toilet compartment in art cabin

FOICISLE

escape hatch, hanging space. lockers, berths convertible to a double, ockers, finished in teak veneer, to a double, emergency stowage

TOILET/SHOWER

cupboards, hanging lockers with zip curtains in waterproof material, shower. Finished in system, basin with pressurised hot and cold Marine WC with inlet and outlet clean laminates. towel rail, mug and paper fitments, seacocks, water

SALOON

berth opposite, tak fixed chart table. Inside shaped settee/berth with second steering - optional. table, shelves a and lockers, teak settee/ veneer.

opposite:

e: Drinks locker, hanging locker

MLLEY

and grill, oven with flame failure device, gimballed with clamp type fiddle rail. Stainless steel sink with pressurised cutlery Calor gas cooker cold stowage Mater system. space. comprising two burners, Good crockery and Tot

AFT CABIN

Double berth fore and aft, dressing opening porthole. with hot and cold pressurised water system. toilet compartment with marine WC and basin hatch. wardrobe Finished in teak veneer. and stowage lockers, opening Separate table,

AFT PEAK

Access to steering position. Emergency tiller supplied when single steering position only fitted. Stowage space.

FORE PEAK

Chain stowage.

AFT COCKPIT

Calor locker/sailbin. Steering pede instrument panel and controls. Seating gas locker. both sides Steering and aft, pedestal, access Double to engine

ENGINE

with standard instrumentation and single diesel Volvo MD21, control. Dipstick in stainless steel. engine, 61 h.p. 02 Dipstick to fuel tank. ess steel. Two bladed comparable replacement, 4 s.h.p. continuous

ELECTRICAL

stern/steaming and deck flood lights. Charging by way of a 12v alternator of 2 heavy duty 12v batteries with 3 way Electric lighting in cabins. Port/sta propeller in bronze. 12v alternator on Port/starboard switch. engine

EQUIPMENT

cleats, one main sheet and cleat, 2 g tracks, sliders and blocks, handrails ventilators, forehatch, fuel and wate fillers, anodised aluminium toe rail. pushpit, Stemhead fitting with chain fairleads, stanchions and chain plates, 4 N plates, 4 mooring cleats and genoa sheet winches with n sheet and cleat, 2 genoa sockets, lifelines, handrails and roller, and water pulpit,

SPARS

halyard. foresail halyards, topping lift In silver anodised aluminium and comprising mast with winches and cleats for main and reefing. Main boom and through mast and burgee roller

RIGGING

Wire. burgee in terylene and flexible galvanised for main running Standing rigging in stainless steel rigging and foresail, comprising rope topping lift tail and Wire halyards

SAILS

Working Mainsail D' SUPPLIED STANDARD

tacks and All sails hanks from a well known sail P. terylene complete with bags, maker.

diaphragm type bilge pump

set OH settee cushions and mattresses

Fitted carpets

EQUIPMENT GENERAL

W mooring sdrew extinguishers

dry powder fire

fenders

Wheel Anchor steering with 15 fathoms OH non calibrated

chain

Compass

Sumlog

Echo sounder on Swinging bracket

First Aid Kit X'

Tool

Log book

Mainsail Emergency coat tiller where second position not

Curtains Automatic in deck FITE extinguisher saloon and aft F. engine cabin room

MOODY 36 DECK The above specification DECK SALOON. m. intended 0 fairly represent

reserved. However the right 40 amend this specification without notice H.